



NORMANN



Click the TurboChef catalogue above,
or scan the code to download.



NORMANN

Blast Chiller - Entry	284
Blast Chiller - Nortech	285
Blast Chiller - Nortech Plus	286
Blast Chiller - Big Boy Roll-in	287
Blast Chiller - Big Boy Panel Unit	288
Blast Chiller - Frame Modular Stand Alone	289

NT & TAS - For orders in these states please
add 5% transport surcharge to your purchase price

Blast Chiller - Entry

- R290 natural refrigerant for improved efficiency and reduced environmental impact
- 4.3" touchscreen interface for simple operation
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal core probe for accurate temperature monitoring
- Large 73mm tray spacing for improved airflow
- Reversible left-hand hinged door for flexible installation
- Door opening hook allows the cavity to breathe when not in use
- Heated door perimeter to reduce condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for enhanced rust protection
- HACCP data collection – Complete download via optional kit
- External condensate drip tray
- **24-month warranty (Terms and conditions apply)**



	Model	Details	Dimensions W x D x H (mm)	Energy Load	RRP ex GST
	ENTRY.3	Free Standing - 3 x 1/1GN Pans Net Capacity - 78 Litres	715 x 695 x 882 Weight: 77kg	0.7kW 10A plug & lead fitted	\$9,040
	ENTRY.5	Free Standing - 5 x 1/1GN Pans Net Capacity - 104 Litres	715 x 695 x 947 Weight: 96kg	0.9kW 10A plug & lead fitted	\$9,820
	ENT.5UC	Undercounter - 5 x 1/1GN Pans Net Capacity - 104 Litres	715 x 695 x 847 Weight: 86kg	0.9kW 10A plug & lead fitted	\$10,200
	ENTRY.10	Free Standing - 10 x 1/1GN Pans Net Capacity - 199 Litres	715 x 695 x 1412 Weight: 120kg	1.6kW 10A plug & lead fitted	\$13,500
	ENTRY.15	Free Standing - 15 x 1/1GN Pans Net Capacity - 292 Litres	715 x 695 x 1921 Weight: 159kg	2.2kW 15A plug & lead fitted	\$19,170
	SPNOR.CAST01	Mobile castor kit Refer to Data Sheets for unit height with castor kit			\$440
	SPNOR.ENTBT00TH	Bluetooth Connectivity			\$450
	CMGE.0927	1/1 GN S/S Grid Rack			\$70

Blast Chiller - Nortech

- Premium high-performance blast chiller
- R290 natural refrigerant for improved efficiency and lower environmental impact
- 7.0" touchscreen interface for simple operation
- Ozone sanitation connection for improved cabinet hygiene (Generator available in options)
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- Large 78mm tray spacing for improved airflow
- WIFI and HACCP connection for data collection
- Door opening hook allows the cavity to breathe when not in use
- Heated door perimeter to reduce condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- Magnetic front panel with large condenser filter for easy access and maintenance
- External condensate drip tray
- Reversible left-hand hinged door (ex factory, on request)
- **24-month warranty (Terms and conditions apply)**



	Model	Details	Dimensions W x D x H (mm)	Energy Load	RRP ex GST
	NAT.5	Free Standing - 5 x 1/1GN Pans Net Capacity - 115 Litres	750 x 864 x 970 Weight: 114kg	1.3kW 10A plug & lead fitted	\$21,750
	NAT.10	Free Standing - 10 x 1/1GN Pans Net Capacity - 228 Litres	750 x 864 x 1620 Weight: 188kg	2.7kW 3Ø + N + E	\$27,700
	NAT.15	Free Standing - 15 x 1/1GN Pans Net Capacity - 341 Litres	750 x 864 x 2020 Weight: 236kg	3.4kW 3Ø + N + E	\$35,500
	SPNOR.OZONEG	Plug in Ozone Generator			\$1,750
	SPNOR.CAST02	Mobile castor kit Refer to Data Sheets for unit height with castor kit			\$620
	SPNOR.PROBE4	Predisposition for 4 probes (includes one probe)-ex factory			\$625
	SPNOR.PROBE	Additional probes (only for predisposition units)			\$630
	CMGE.0927	1/1 GN S/S Grid Rack			\$70

Blast Chiller - Nortech Plus

- Premium high-performance multi-function blast chiller with low-temperature cooking up to 85°C and controlled humidity
- R290 natural refrigerant for improved efficiency and lower environmental impact
- 7.0" touchscreen interface for simple operation
- Integrated ozone sanitation for improved cabinet hygiene
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal multi-point core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- Large 78mm tray spacing for improved airflow
- WIFI and HACCP connection for data collection
- Door opening hook allows the cavity to breathe when not in use
- Heated door perimeter to reduce condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- Magnetic front panel with large condenser filter for easy access and maintenance
- External condensate drip tray
- Reversible left-hand hinged door (ex factory, on request)
- **24-month warranty (Terms and conditions apply)**



	Model	Details	Dimensions W x D x H (mm)	Energy Load	RRP ex GST
	PLUS.5.SF	Free Standing - 5 x 1/1GN Pans Net Capacity - 115 Litres Includes - Standard Filter	750 x 864 x 970 Weight: 124kg	1.6kW 10A plug & lead fitted	\$29,700
	PLUS.5.RO	Free Standing - 5 x 1/1GN Pans Net Capacity - 115 Litres Includes - Reverse Osmosis Filter	750 x 864 x 970 Weight: 124kg	1.6kW 10A plug & lead fitted	\$31,200
	PLUS.10.SF	Free Standing - 10 x 1/1GN Pans Net Capacity - 228 Litres Includes - Standard Filter	750 x 864 x 1620 Weight: 198kg	3.1kW 3Ø + N + E	\$38,100
	PLUS.10.RO	Free Standing - 10 x 1/1GN Pans Net Capacity - 228 Litres Includes - Reverse Osmosis Filter	750 x 864 x 1620 Weight: 198kg	3.1kW 3Ø + N + E	\$39,600
	PLUS.15.SF	Free Standing - 15 x 1/1GN Pans Net Capacity - 341 Litres Includes - Standard Filter	750 x 864 x 2020 Weight: 264kg	4.3kW 3Ø + N + E	\$51,200
	PLUS.15.RO	Free Standing - 15 x 1/1GN Pans Net Capacity - 341 Litres Includes - Reverse Osmosis Filter	750 x 864 x 2020 Weight: 264kg	4.3kW 3Ø + N + E	\$52,700
	SPNOR.CAST02	Mobile castor kit Refer to Data Sheets for unit height with castor kit			\$620
	SPNOR.PROBE4	Predisposition for 4 probes (includes one probe)-ex factory			\$620
	SPNOR.PROBE	Additional probes (only for predisposition units)			\$630
	CMGE.0927	1/1 GN S/S Grid Rack			\$70

Blast Chiller - Big Boy Roll-in

- Premium self contained blast chiller designed for fast reliable performance (excludes BB40 - Remote unit)
- Complete unibody construction in durable 304 grade stainless steel
- R290 natural refrigerant for improved efficiency and lower environmental impact
- 7.0" touchscreen interface for simple operation and bumper protection
- Cell sanitising - Ozone sanitation plug in connection point for improved cabinet hygiene
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Internal cavity and condenser bumpers to protect key components
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal multi core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- WIFI and HACCP connection for data collection
- Heated door perimeter for reduced condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- External drain tube for easy condensate removal
- **24-month warranty (Terms and conditions apply)**



	Model	Details	Dimensions W x D x H (mm)		RRP ex GST
	BB20	Floor Mount - 10 x 1/1GN Pans Net Capacity - 1018 Litres	1210 x 1101 x 2378 Weight: 380kg	4.7kW 3Ø + N + E	\$54,750
	BB20.RO	Free Standing Roll Out - 10 x 1/1GN Pans Net Capacity - 1018 Litres	1210 x 1101 x 2280 Weight: 380kg	4.7kW 3Ø + N + E	\$57,200
	BB40	Floor Mount - 20 x 1/1GN Pans Net Capacity - 1592 Litres Remote Unit	1241 x 1390 x 2222 Weight: 340kg	1.8kW 3Ø + N + E	\$50,400
	CMGE.0927	1/1 GN S/S Grid Rack			\$70
	Right Hinged Door	Ex Factory - P.O.A			P.O.A
	CO2 Predisposition				P.O.A

Blast Chiller - Big Boy Panel Unit

- Premium blast chilling for fast reliable performance, supplied flat packed
- Designed for connection to a remote condensing unit (condensation unit not included)
- Panels are constructed with durable 304 stainless steel
- 7.0" touchscreen interface for simple operation
- Supplied complete with entry ramp for safe trolley access
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- WIFI and HACCP connection for data collection
- Reversible left-hand hinged door for flexible installation (refer to accessories)
- Heated door perimeter for reduced condensation
- Rounded internal corners for easier cleaning and improved hygiene
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- External drain tube for easy condensate removal
- **24-month warranty (Terms and conditions apply)**



	Model	Details	Dimensions W x D x H (mm)	Energy Load	RRP ex GST
	BBF1	Floor Mount - 1 x 2/1GN Compatible trolley configurations: • 2 x 1/1GN Pan Trolley • 1 x 2/1GN Pan Trolley • 2 x EN60/40 Pan Trolley • 1 x EN60/80 Pan Trolley Net Capacity - 1776 Litres	1500 x 1400 x 2395 Weight: 500kg	0.6kW 10A plug & lead fitted	P.O.A
	BBF2	Floor Mount - 2 x 2/1GN Compatible trolley configurations: • 4 x 1/1GN Pan Trolley • 2 x 2/1GN Pan Trolley • 4 x EN60/40 Pan Trolley • 2 x EN60/80 Pan Trolley Net Capacity - 3108 Litres	1500 x 2450 x 2395 Weight: 600kg	1.2kW 10A plug & lead fitted	P.O.A
	BBF3	Floor Mount - 3 x 2/1GN Compatible trolley configurations: • 6 x 1/1GN Pan Trolley • 3 x 2/1GN Pan Trolley • 6 x EN60/40 Pan Trolley • 3 x EN60/80 Pan Trolley Net Capacity - 4884 Litres	1500 x 3500 x 2395 Weight: 870kg	1.7kW 10A plug & lead fitted	P.O.A
	BBF4	Floor Mount - 4 x 2/1GN Compatible trolley configurations: • 8 x 1/1GN Pan Trolley • 4 x 2/1GN Pan Trolley • 8 x EN60/40 Pan Trolley • 4 x EN60/80 Pan Trolley Net Capacity - 6216 Litres	1500 x 4550 x 2395 Weight: 880kg	2.2kW 10A plug & lead fitted	P.O.A
	CMGE.0927	1/1 GN S/S Grid Rack			\$70
	Right Hinged Door	Ex Factory - P.O.A			P.O.A

Blast Chiller - Frame Modular Stand Alone

- Independent modular system to integrate easily into new or existing coldrooms
- Remote condensing unit (condensation unit not included)
- 7.0" touchscreen interface for simple operation
- Soft and hard blast chilling, plus soft and hard blast freezing for flexible product control
- Dedicated cycles for pre-cooling, fish sanitation, ice cream hardening, bottle cooling and pastry and air defrosting
- Special cycle library with built-in recipes to support consistent results
- Internal multi core probe for accurate temperature monitoring
- Adjustable fan speeds for improved product control
- WIFI and HACCP connection for data collection
- CFC free high density polyurethane insulation
- Cataphoresis treated evaporator for improved rust protection
- External drain tube for easy condensate removal
- **24-month warranty (Terms and conditions apply)**



Model	Details	Dimensions W x D x H (mm)	Energy Load	RRP ex GST
FRAME	Frame Stand Alone - 1 x Trolley Remote condensing unit	1015 x 410 x 2094 Weight: 91kg	1.4kW 10A plug & lead fitted	P.O.A
Remote controller (at 3 metres)				P.O.A

